SPRADLING®

Linetex®
PRELIMINARY SPECIFICATION

COMMERCIAL SPECIFICATION

GENERAL

Weight	665 ± 65 g/m²
Width	1.37 m
Temperature Reduction Treatment	
Topcoat	PERMABLOK3® ADVANCED VINYL PROTECTION PLUS+
Roll Length	30 m
Composition	PVC
Gauge	1.10 ± 0.16 mm

BACKING

Description	Jerry
Weight	120 g/m² - ISO 2286-2
Type	Polyester

SUSTAINABLE PRODUCT PROFILE

ATTRIBUTES

Phthalate Free	REACH Annex XVII, Items 51 & 52 CERTIFICATE	Skin Safe - Sensitization	ISO 10993-10 CERTIFICATE
Skin Safe - Irritation	ISO 10993-23 CERTIFICATE		

CERTIFICATIONS

EPD INTERNATIONAL EPD SYSTEM

*To see the certification document, click on the PDF logo
*To know more about each certification, click here

SEALS WE CONTRIBUTE TO

INTERNATIONAL WELL BUILDING INSTITUTE™

SUSTAINABLE MANUFACTURING CERTIFICATIONS

CARBONO NEUTRO CERTIFICADO ISO 14001 ISO 45001 ISO 50001

COMPLIANCES

REACH COMPLIANT RoHS COMPLIANT

ADDITIONAL TESTS

Tensile Strength Test - ISO 1421 M1

N(Min.)	Warp	268
	Fill	361

Elongation At Break Test - ISO 1421 M1

%(Ave.)	Warp	109
	Fill	62

Tear Strength Test - ISO 4674-1 MB

N(Min.)	Warp	25
	Fill	38

Stitching Strength Test - DIN 54301

N(Min.)	Warp	46
	Fill	56

Adhesion Test - ISO 2411

N/5cm(Min.)	Warp	9.1
	Fill	20

Abrasion Resistant III Test - UNE - EN ISO 12947 pdf - Certificate

MARTINDALE		> 100,000 Cycles

Crocking Resistant I Test (ISO 105-X12)

---------	Wet	5 - 4/5
	Dry	5 - 4/5

UV stability Test pdf - Certificate

Xenotest	ISO 105-B02 Blue Wool	Cal≥7 1,000 Hours = Passes / Pasa
Weather-Ometer	ISO 105-B04 - Colour fastness to artificial weathering	Rating/Cal ≥ 4 (Passes) - Grey Scale - 1,000 Hours

ADDITIONAL TESTS

Cold Crack Test pdf - Certificate	
CFFA-6a	-29 °C

FLAME RETARDANCY

US FMVSS 302	Pass	US NFPA 260 - Class 1	Pass
US UFAC Fabric Class 1	Pass	US CAL TB 117-2013, Section 1	Pass
EU EN 1021 Part 1 & 2	Pass	DE DIN 4102	B2
EU/US IMO FTPC Part 8	Pass		

This term and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.

OTHER ATTRIBUTES

Bacterial Resistant	AATCC 147	Anti Static	ASTM D257 Certificate
Mildew Resistant	No Growth (NG)	Mildew Resistance Method	ASTM G21
Pink Stain Resistant	ASTM E1428 Certificate	Sulfide Stain Resistance	FISHER BODY TM 31-12 Certificate
Temperature Reduction Treatment	ASTM D4803 Certificate	Antistatic	Yes
MED	Yes	UKCA	Yes

MANUFACTURING CERTIFICATIONS

2923/2025 8512/2025

WARRANTY

*Terms and Conditions apply.

Note: The data correspond to minimum results of the statistical analysis. The information included in the specification is subject to change.
The indicated data corresponding to the material's physical characteristics are results of test conducted under standard procedures and are subject to variation. We therefore recommend our customers to evaluate the material with regard to the specific requirements and application(s) before specifying. For additional information, please contact your sales representative.
These terms and any corresponding data refer to the typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.
Spradling group does not assume any responsibility for any damages resulting from improper applications.
Spradling group does not guarantee exact color matches as slight variations in production and stock may occur, as such lot separations is suggested.
Spradling group reserves the right to modify technical sheets without notification.

For a better experience, we recommend opening the file directly in a PDF viewer, and not in the browser.

Conscious of our impact. Designed for the long run.

SPRADLING®
For the long run

V. 8 | Date: February 9, 2026